Camera Models D14



Model: Indoor/Outdoor:

Lenses: (eq. 35mm)

Resolution:

Pan/Tilt/Zoom: Frame Rate (max.): Sensitivity: Interfaces: Internal DVR-Audio/Telephony: Power Sup. • In/Out:

Arming • Triggering: External Storage:

Software Features:

Prices:

D14Di-IT

Dual lens Indoor, IP54, -30 to +60 °C 2 Super Wide Angles (22mm, 90°, F 2.0) 32mm, 43mm, 65mm, 135mm 2 x VGA (je 640x480), color & B/W

Continuous 8x zoom & pan/tilt (digital) 30 fps VGA • 30 fps MEGA 1 lux (t=1/60s) • 0.05 lux (t=1/1s) Ethernet 10/100, RS232, MiniUSB, MxBus Up to 64 GB with MicroSD card Bidirectional, IP telephony (VoIP) PoE or MX30V

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search 365 day schedule • Multiple events Up to 1 TB on PC/Server/NAS

£968 (MX-D14Di-IT)

D14Di-Sec

2 Super Wide Angles (22mm, 90°, F 2.0) 32mm, 43mm, 65mm, 135mm

Dual lens Indoor, IP54, -30 to +60 °C

1 x 3MEGA (2048x1536 pixels), color 1 x MEGA (1280x960 pixels), B/W Continuous 8x zoom & pan/tilt (digital)

30 fps VGA • 30 fps MEGA • 20 fps 3MEGA

1 lux (t=1/60s) • 0.05 lux (t=1/1s) Ethernet 10/100, RS232, MiniUSB, MxBus

Up to 64 GB with MicroSD card Bidirectional, IP telephony (VoIP) PoE or MX30V

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search 365 day schedule • Multiple events Up to 1 TB on PC/Server/NAS

£1,158 (MX-D14Di-Sec)



D14Di-Sec-180°

Dual lens Indoor, IP54, -30 to +60 °C 2 Super Wide Angles (22mm, 90°, F 2.0)

2 x MEGA (2560x960 pixels), B/W

Continuous 8x zoom & pan/tilt (digital) 30 fps VGA • 30 fps MEGA • 20 fps 3MEGA 1 lux (t=1/60s) • 0.05 lux (t=1/1s) Ethernet 10/100, RS232, MiniUSB, MxBus Up to 64 GB with MicroSD card Bidirectional, IP telephony (VoIP) PoE or MX30V

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search 365 day schedule • Multiple events Up to 1 TB on PC/Server/NAS

£1,158 (MX-D14Di-Sec-180°)

Accessories D14



Part Name: Description:

Prices:

D14 Pole and Corner Mount

- 3mm stainless steel, powder-coated
- Pole diam.: 60 to 180mm

£88 (MX-MH-Dome-ESWS)

• Incl. mounting supplies



D14 Wall Mount

- Weatherproof (IP65) for D14D-Dome
- Robust and UV resistant PBT
- Covers RJ45 wall outlets and PatchBox
- Incl. ETH patch cable (1m)



£138 (MX-WH-Dome)



Part Name:

Description:

Part Name:

Description:

Part Name:

Description:

Prices:

Prices:

D14 Vandalism Set

- Reinforced dome (3mm Polyc.)
- Stainless steel vandalism ring (matt or polished)

Prices: £138 (MX-D14-Vandal-ESPO/ESMA)

D14 Vandalism Set

Reinforced dome (3mm Polyc.)

Stainless steel vandalism ring (white, silver or black powder-coated)

£138 (MX-D14-Vandal-PUWH/PUGR/PUBL)

D14 mounted to corner D14 mounted to pole

Accessories All Cams





PoE Power Adapter Set

- Power supply via network cablina
- All cameras supplied by PoE

£98 (MX-NPA-PoE-Set-INT)





Network Power Rack for 4/8/20 cameras

- Power supply for DIN rails
- For M12, M22, D12, D22, Q22,V12, DevKit series

from £368 (MX-NPR-4/NPR-8/NPR-20)





Weatherproof universal network connector for installation cable, MOBOTIX patch cable and standard patch cable

£868 (MX-OPT-Patch1-EXT)





Mx2Wire Pure White

- Ethernet and PoE using two-wire cable
- Up to 500 meters/up to 30 Mbps (netto)

Set price (2 units) £278 (MX-2Wire-Set-PW)

7 watts via PoE



ExtIO

- Each with 2 In- and Output contacts 8-24V
- Microphone with adjustable volume control, speaker, status LEDs
- USB interface, illumination sensor,
- Temperature sensor, 2 buttons • For all cameras except M1, M10, D10 und V10
- £188 (MX-ExtIO)

MSRP (Manufacturer's suggested retail prices) • Prices ex-works Langmeil, Germany (EXW) • Excluding VAT and any other handling charges • Calculated at FXR 1EUR = 0,9194GBP,





Cam-IO-PoE/AC/ACplus

- Interface for external sensors and equipment (door contact, light, etc.)
- 2xRelais-Out, 2xInput, backup, audio
- Power supply via network / 230V / 230V battery buffered • Compatible with M12 cameras

from £278 (MX-CAMIO)

21.01.2009 • Information subject to change without notice! • Date: 10/2011 • © MOBOTIX AG